

INDOOR TAPS

COMPATIBLE WITH DOCSIS 3.1

REF.	ART. NR.	DESCRIPTION	EAN 13
451803	AZ114D	TAP 5...1218MHz "F" 1D 14dB	8424450192955
451903	AZ117D	TAP 5...1218MHz "F" 1D 17dB	8424450192962






▲ 451803



New taps range with one derivation output. It stands out their small dimensions and easy installation thanks to its screw mounting.

- Distribution elements compatible with the DOCSIS 3.1 standard
- Frequency range of 5...1218MHz
- High shielding against interferences thanks to its chassis injected with Zamak
- It includes ground connection



REF.	ART. NR.	 mm	 g	 U./Pack.
451803	AZ114D	53 x 47 x 20	60	1/bag - 10/box
451903	AZ117D	53 x 47 x 20	60	1/bag - 10/box



Reference			451803	451903
Connector type			F - Female	
Frequency range	MHz		5...1218	
Derivations	no.		1	
Insertion loss (Input/Output)	dB		1 ± 0,6	0,9 ± 0,6
Derivation loss (Input/Derivation)	dB		14 ± 1,5	17 ± 1,5
Insulation	dB		> 20	
Shielding	5-30MHz	dB	≥85	
	30-300MHz		≥85	
	300-470MHz		≥80	
	470-1000MHz		≥75	
	950-1218MHz		≥55	