

ABUS Smart Security World Wi-Fi Pan/Tilt Indoor Camera

Art. no. PPIC32020

Page 1 of 3



- For effective, all-round surveillance of indoor areas with pan/tilt and intercom function
- Full HD 1080p resolution and infrared night vision function for brilliant image quality
- Controllable via the app with a 270° pan and 90° tilt area
- Integrated microphone and loudspeaker for two-way communication via the app
- Camera movement can quickly and easily be controlled on three individually configured positions (three preset positions)
- Guided step-by-step installation via the app (iOS, Android)
- Recording to SD card with up to 128 GB (accessory)
- Direct notification via email and push service as well as automatic recording when motion detection is set up
- Low network load thanks to high data compression (H.264 High Profile compression)

The ABUS Smart Security World Wi-Fi Pan/Tilt Camera with Full HD 1080p resolution and infrared night vision function always provides a brilliant image quality and a full overview. The recording range can be controlled via the app and has a swivel range (right–left) of 270° and a tilting range (up–down) of 90° for 360° surveillance. One special feature of the camera is the integrated two-way talkback function that enables two-way communication. As such, this camera is suitable for indoor monitoring or can be used, for example, as a baby monitor.

Event notification and mobile access

Operation of and access to this app camera are exclusively via the app – with no PC, web browser or additional software. If desired, you will be informed of incidents by email or push notification and can take a snapshot or access the corresponding video image data using the app. Movements in the camera's field of vision trigger recording to the SD card. With the app, you always have access to the image material. The compressed data transmission means hardly any burden is placed on the network.

Smart Security World Ready

The ABUS Smart Security World Wi-Fi Pan/Tilt Camera is part of the Smart Security World and is therefore not only functional, but is also fully integrated into the Smartvest wireless alarm system – as such, during installation

ABUS Smart Security World Wi-Fi Pan/Tilt Indoor Camera

Art. no. PPIC32020

Page 2 of 3

there are no concessions in terms of convenience, and users simply follow the intuitive step-by-step installation instructions.

Information on the night vision function

The effective IR range will depend on the installation location.

ABUS Smart Security World Wi-Fi Pan/Tilt Indoor Camera

Art. no. PPIC32020

Page 3 of 3

Technical Data:

Audio bitrate	16 Kbit/s
Channel width	20 MHz
Color	White
Technology	IP
Compatible with Secvest	No
Compatible with wAppLoxx	No
Compatible with Smartvest	Yes
Vertical angle of view	45 °
Min. humidity	20
Basic event	Software + Motion Mask
Dimensions	(B x L x H) 115 x 92 x 118 mm
Alarming	Push notification / E-Mail
Number of presets	3
Resolution modes	Full HD (1080p) / HD (720p) / VGA (480p)
Recording modes	Manual / motion detection
Image sensor	1/2,7" CMOS
Focal length	4 mm
Gross weight	0,85 kg
Frequency range	2,400 –2,485 GHz
Wireless range	(Depending on installation) 20 - 50 m
Housing material	Plastic
Simultaneous network access	3
Horizontal angle of view	90 °
IR LEDs	Yes
IR range (up to)	12 m
IR cut filter	Yes
Compatible with	Smartvest / SmartFriendsBox
Loudspeaker	Yes
Power consumption	4,5 W
Max. resolution @ frame rate	Full HD (1080p) @ 20fps

Max. operating temperature	50 °C
Max. humidity	90 %
Microphone	Yes
Min. operating temperature	-10 °C
Minimum illumination (color)	1 lx
Minimum illumination (IR)	0 lx
Net weight	0,34 kg
Network protocols	TCP/IP, UDP, SMTP, NTP, DHCP, ARP
Network access	RJ-45 socket (10/100 Mbps)
Wi-Fi network access	IEEE 802.11 b/g/n
Optical wavelength	850 nm
Pan/tilt area	270° Horizontal / 90° Vertical
Transmission power	11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm
Sensitivity	-90 dBm
Software	App: ABUS App2Cam Plus (Android/iOS)
DC voltage supply	5 V
Storage medium	Micro-SD (128GB)
Connector type	DC-plug: 3,5 x 1,35mm
Day/night switching	Auto
Encryption	AES 128bit, WPA/WPA2-PSK
Video compression	H.264
Pre-alarm/post-alarm memory	2 Sec
White balance	AWB