

# COMPRESSION “F” - “F” COAXIAL CABLE LEAD




## HIGH SHIELDING, CLASS A+ AND LOW ATTENUATION

REF.	ART. NR	DESCRIPTION	EAN 13
3851	FS-FS2015	CABLE LEAD COMPRESSION F - F WHITE 1.5m	4031136022068
385101	FS-FS2030	CABLE LEAD COMPRESSION F - F WHITE 3m	4031136022075
385102	FS-FS2050	CABLE LEAD COMPRESSION F - F WHITE 5m	4031136022082



A cable lead pre-terminated with compression F connectors (Ref. 3802) and made with a trishield Class A+ coaxial cable: the SK2000+ (ref. 4138xx).



REF.	ART. NR.	 m	 Grs	 Pack u.
3851	FS-FS2015	1,5	109	30
385101	FS-FS2030	3	187	20
385102	FS-FS2050	5	229	15



Ref. / Art.Nr.			3851xx / FS-FS20xx
Cable type			Class A+
	Ø	mm	1.02
	Material	-	Cu (copper)
Inner conductor	Resistance	Ohm/Km	22
	Ø	mm	4.6
	Material	-	PEE (foam polyethylene)
Over lapped foil	Material	-	Aluminium + Polyester
Braid	Material		CuSn (tinned copper)
	Resistance	Ohm/Km	10.5
	Coverage	%	82
2nd shielding film	-		Yes
Outer sheath	Ø	mm	6.7
	Material	-	PVC (polyvinyle clorhidre)
Minimum bending radius	mm		33,5
Shielding at 1GHz	dB		>95 (typ. 125)
Capacitance	pF/m		54
Impedance	Ohm		75
Velocity ratio	%		84
Attenuations dB/m			
Frequency (MHz)	200		0.09
	500		0.14
	800		0.18
	1000		0.21
	1350		0.25
	1750		0.28
	2050		0.31
	2300		0.32