

Secvest Wireless Remote Control

Art.-Nr. FUBE50012



- Intuitive remote control with user-friendly key symbols
- For convenient operation of the alarm panel
- 8 LEDs for reporting and displaying the current system status
- Operation using the "arm", "disarm" and "status query" keys
- Freely programmable button for switching outputs (not on Secvest IP)
- Manual panic alarm as possible (not on Secvest IP)

Convenient operation of the alarm control panel

The wireless remote control is a practical accessory for the Secvest wireless alarm system. Its use enables the system to be operated at the simple touch of a button. It also allows the current system status to be queried at any time.

Reliable arming at long range

The remote control facilitates arming and disarming of the alarm system – even at great distances. Thanks to 8 integrated LEDs, real-time feedback is provided regarding changes to the system status. The transmission range is approx. 30 metres.

Rapid assistance in an emergency

Simultaneously pressing the 'arm' and 'disarm' buttons triggers a panic alarm. This protects both people and valuables effectively.

Display of additional information

By pressing the third button, important information about the status of the alarm control panel can be queried (armed, disarmed, internal protection active, fault). Feedback is immediately displayed on the remote control.

Secvest Wireless Remote Control

Art.-Nr. FUBE50012

Useful convenience functions

The fourth button allows custom configuration, it can be set to control a garage door, for example . This button can be programmed directly on the alarm control panel.

Secvest Wireless Remote Control

Art.-Nr. FUBE50012

Technical Data

Battery type	CR2450 3V Li-Mn (FU2987)
Certifications	VdS (H 114001)
DC voltage supply	3V
Display	LED
Environmental class	II
Height	17mm
Housing material	ABS
Language of instructions	DE, UK, FR, NL, DK, PL
Length	62mm
Max. battery life	2year(s)
Max. humidity	75%
Max. operating temperature	40°C
Max. receiving range (building)	30m
Max. receiving range (outdoors)	200m

Max. sending range (building)	30m
Max. sending range (outdoors)	200m
Min. operating temperature	-10°C
Modulation	FM
Net weight	0.03kg
Packaging language	DE, UK, FR, NL, DK, PL, ES, SE, IT
Radio frequency	868MHz
Security level	2
Transmission power	10
Voltage monitoring	Yes
Width	362mm